

## **FUJINON**

Ver 2.2

| 型番                       | Product Name  | Ver.2.2<br>CF35ZA-1S |
|--------------------------|---|----------------------|
| ·                        | Focal length [mm]   | 35                   |
| 焦点距離 [mm]                | (design value)  | (34.78)              |
| 絞り範囲 (F値)                | Iris range (Fnumber)  | F1.8-F16             |
| 画角 (H × V)               | Angle of view   | 23.0° × 17.3° (1.1") |
| フォーカス範囲 (レンズメカ先端より) [mm] | Working distance (from front of lens barrel) [mm]                             | ∞ - 200              |
| 操作方法:フォーカス               | Operation of focus  | Manual               |
| 操作方法:アイリス                | Operation of iris   | Manual               |
| フィルタ径 [mm]               | Filter thread [mm]  | M37.5 × 0.5          |
| マウント                     | Mount   | C-mount              |
| 質量(約)[g]                 | Weight (approx.) [g]  | 165                  |
| 適合センサーサイズ(標準)            | Sensor size (std.)  | 1.1" (2.5μm)         |
| 適合センサーサイズ(最大)            | Sensor size (max.)  | 4/3" (3.45µm)        |
| バックフォーカス(空気換算長)[mm]      | Back focal length (in air) [mm]   | 21.3                 |
| フランジバック [mm]             | Flange back [mm]  | 17.53                |
| 入射瞳位置 (マウント面から) [mm]     | Entrance pupil position (from Mount) [mm]                                     | -26.59               |
| 射出瞳位置 (結像面より) [mm]       | Exit pupil position (from image plane) [mm]                                   | -102.02              |
| 前側主点 (マウント面から) [mm]      | Front principal point (from Mount) [mm]                                       | -4.54                |
| 後側主点 (マウント面から) [mm]      | Rear principal point (from Mount) [mm]  | -17.25               |
| 主点間隔 [mm]                | Distance between the principal points [mm]                                    | -12.71               |
| TVディストーション [%]           | TV distortion [%]   | -0.32                |
| 外形寸法 [mm]                | Dimension [mm]  | φ39 × 67.3           |
| 主光線入射角度 [°]              | Chief Ray Angle [°]   | 4.53                 |
| 周辺光量比 (F4.0·対角端) [%]     | Relative illumination [%] (Aperture: F4.0, Image height: at diagonal)         | 93                   |
| 周辺光量比(開放・対角端)[%]         | Relative illumination [%] (Aperture: at full open, Image height: at diagonal) | 37                   |
| 使用温度範囲                   | Operation Temperature Range   | -10°C ∼ +50°C        |
| 保存温度範囲                   | Storage Temperature Range   | -30°C ∼ +60°C        |

These specifications are subject to change without notice.