

Revoria Press SC285S / SC285 Functions & Specifications

Specialty toners are available in “Revoria Press SC285S” or “Revoria Press SC285 equipped with the specialty toner option”. Specialty toners can be used in addition to CMYK for overprinting.

Basic Specifications

Item		Description
Color capability		Full color
Print resolution		2,400 x 2,400 dpi
Warm-up time		300 seconds or less (room temperature 23°C)
Continuous print speed*1		A4: 85 ppm, A3: 47 ppm
Paper size*2	Tray 1, 2, 3	140 x 182 mm to 330 x 488 mm
	Bypass tray (Optional)*3	90 x 146 mm to 330 x 1,300 mm *4
Paper weight	Tray 1, 2, 3	64 to 256 gsm
	Bypass tray (Optional) *3	52 to 300 gsm*5
Paper capacity*6	Tray 1, 2, 3	570 sheets x 3-tray
	Bypass tray (Optional) *3	250 sheets
Power supply		Single-phase AC200-240 V +/-10%, 20 A, 50/60 Hz, ground connection Note: For US, Canada, Single-phase AC208-240 V +/-10%, 16 A, 50/60 Hz, ground connection
Maximum power consumption		4.8 kW (in case of 240 V) Note: For US, Canada, 4.224 kW (in case of 240 V)
Dimensions*7		W 1,159 x D 858 x H 1,310 mm
Weight*8		288 kg or less (include bypass tray) 282 kg or less (exclude bypass tray)

*1: When continuously printing a single sided document. 52 to 350 gsm, uncoated paper. Print speed may be reduced depending on conditions of output data, on whether specialty toner is used, on whether auto image quality adjustment is performed, on whether the job includes a mixture of paper sizes and types, and other reasons.

*2: Image loss width: lead edge 4.0 mm, trail edge 2.0 mm, front 2.0 mm, rear 2.0 mm.

*3: When the optional bypass tray (Multi Sheet Inserter for Banner Print) is directly connected to the printer unit.

*4: Up to 330 x 660 mm paper is supported in duplex automatic printing. To use paper longer than 488 mm, feed and output options compatible with that paper size are required.

*5: Sheets longer than 488 mm can be used with weights from 52 to 220 gsm.

*6: 82 gsm paper.

*7: Printer unit + Bypass tray (Multi Sheet Inserter for Banner Print). Excludes feeding / output options. Bypass tray is closed.

*8: Printer unit + Bypass tray (Multi Sheet Inserter for Banner Print). Excludes feeding / output options. Excludes toner cartridges.

When connecting the paper feed option, please be aware that the weight of the bypass tray may be included in the feed option.

Internal Print Function

Item	Description
Continuous print speed	[PCL Driver] Same as the Basic Specifications
Paper size	[PCL Driver] Same as the Basic Specifications
Data resolution	[PCL Driver] Standard: 2,400 x 2,400 dpi, High Resolution: 2,400 x 2,400 dpi
PDL (Page Description Language)	PCL
Printer driver OS ^{*1}	[PCL Driver] Windows 11 (64bit), Windows 10 (32bit / 64bit), Windows Server 2022 (64bit), Windows Server 2019 (64bit), Windows Server 2016 (64bit)
Connecting port	Ethernet 1000BASE-T / 100BASE-TX / 10BASE-T, USB2.0

*1: Please refer to our official website for the latest supported OS.

Scan Function

Item	Description
Type	Color scanner
Document size	[Document glass / Duplex Automatic Document Feeder] Standard size: Max A3, 11 × 17", Min A6, 5.5 × 8.5" Custom size: 15 × 15 mm to 297 × 432 mm
Scan resolution	600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 200 dpi
Scan speed	Same as the "Scan speed" of the Duplex Automatic Document Feeder
Scan output	Store to folder (TWAIN interface support), Scan to PC, Scan to e-mail

Copy Function

Item	Description
Document size	[Document glass / Duplex Automatic Document Feeder] Standard size: Max A3, 11 × 17", Min A6, 5.5 × 8.5" Custom size: 15 × 15 mm to 297 × 432 mm
Paper size ^{*1}	Standard size: Max A3, 11 × 17", Min A6, 5.5 × 8.5" Custom size: 90 × 146 mm to 330 × 1,300 mm ^{*2}
Scan resolution	600 x 600 dpi
Print resolution	2,400 x 2,400 dpi (Text-Photo / Photo), 600 x 600 dpi (Text / Map)
Tone	256 levels of each color
First copy output time ^{*3}	B/W: 5.2 sec. or less (A4 / Monochrome priority mode) Color: 9.0 sec. or less (A4 / Color priority mode)

*1: Image loss width: Lead edge 4.0 mm, Trail edge 2.0 mm, Front 2.0 mm, Rear 2.0 mm.

*2: To use paper longer than 488 mm, feed and output options compatible with that paper size are required.

*3: When the original is placed on the document glass, paper is fed from tray 1, the document is copied from simplex-to-simplex output and a copy is output to the Offset Catch Tray.

Duplex Automatic Document Feeder

Item		Description
Document size		Please refer Scan function and Copy function.
Document paper weight		38 to 200 gsm (In Duplex: 50 to 200 gsm)
Document capacity* ¹		250 sheets
Scan speed* ²	Copy	B/W: 90 ppm, Color: 90 ppm (A4 LEF, 1-sided)
	Scan	1-sided scanning: 135 ppm, 2-sided scanning: 270 ppm [Standard document (A4), 200 dpi, store to folder]

*1 80 gsm paper.

*2 The scanning speed varies depending on the documents.

Print Server [Revoria Flow SC21 / SC22]

Item	Description	
	Revoria Flow SC21	Revoria Flow SC22 * ¹
Type	External	
CPU	Intel® Xeon® E-2226GE Processor (3.4- 4.6 GHz)	Intel® Core™ i3-9100E Processor (3.1-3.7 GHz)
Memory	32 GB (Max 32 GB)	16 GB (Max 32 GB, Optional)
Storage device	Hard disk: 4 TB (System), SSD: 1,920 GB, DVD Multi drive	Hard disk: 1 TB (System), SSD (optional): 1,920 GB, DVD Multi Drive
Server OS	Windows 10 IoT Enterprise LTSC 2021 (64bit)	
Print data format	PS, PDF2.0, PDF/X-1a, PDF/X-3, PDF/X-4, PDF/X-5, EPS, TIFF, JPEG, PDF/VT, PPML	
RIP type	Adobe® PostScript® 3™ (Configurable PostScript Interpreter), Adobe® PDF Print Engine 6	Adobe® PostScript® 3™ (Configurable PostScript Interpreter), Adobe® PDF Print Engine 6 (Optional*) * Available of the option depends on the location.
Printer driver OS* ²	Windows 11 (64bit), Windows 10 (32bit / 64bit), Windows Server 2025 (64bit), Windows Server 2022 (64bit), Windows Server 2019 (64bit), Windows Server 2016 (64bit), macOS 15 / 14 / 13 / 12 / 11	
Connecting port	Ethernet 1000BASE-T / 100BASE-TX / 10BASE-T x 2	
Network protocol	LPR, FTP, SMB, HTTP, JDF, SNMP, Bonjour	
Power supply	Single-phase AC100-240 V +/- 10%, 3.6 A (100 V) / 1.5 A (240 V), 50/60 Hz, ground connection	
Maximum power consumption	0.4 kW (in case of 240 V)	
Dimensions* ³	W 170 x D 403x H 358 mm	
Weight* ³	8.9 kg or less	

*1: Optional memory is required for duplex printing longer than 660 mm paper. Optional memory is required for printing longer than 660 mm paper at 1,200 x 1,200 dpi.

*2: Please refer to our official website for the latest supported OS.

*3: Print Server only. Excludes monitor, mouse, and keyboard.

High Capacity Feeder B1 (Optional)

Item	Description
Paper size	Max A4, Letter, Min JIS B5, 7.25 x 10.5"
Paper weight	64 to 220 gsm
Paper capacity ^{*1}	2,100 sheets x 1-tray
Dimensions	W 389 x D 610 x H 377 mm
Weight ^{*2}	29 kg or less

Note: Optional bypass tray (Multi Sheet Inserter for Banner Print) is required. It is connected to the printer directly.

*1 82 gsm paper.

*2 Excludes bypass tray (Multi Sheet Inserter for Banner Print).

High Capacity Feeder B1-S / High Capacity Feeder C3-DS / 2nd High Capacity Feeder C1-DS (Optional)

Item		Description		
		High Capacity Feeder B1-S	High Capacity Feeder C3-DS	2nd High Capacity Feeder C1-DS
Paper size	High-capacity tray ^{*1}	Standard size: Max 13 x 19", SRA3, A3, Min 4 x 6", JIS B5 Custom size: 98 x 148 mm to 330 x 488 mm	Standard size: Max 13 x 19", SRA3, A3, Min 4 x 6", JIS B5 Custom size: 98 x 148 mm to 330 x 488 mm	Standard size: Max 13 x 19", SRA3, A3, Min 4 x 6", JIS B5 Custom size: 98 x 148 mm to 330 x 488 mm
	Bypass tray (Optional)	Standard size: Max 13 x 19", SRA3, A3, Min A6, 5.5 x 8.5" Custom size: 90 x 146 mm to 330 x 660 mm	Standard size: Max 13 x 19", SRA3, A3, Min A6, 5.5 x 8.5" Custom size: 90 x 146 mm to 330 x 660 mm	-
Paper weight	High-capacity tray	52 to 300 gsm	52 to 350 gsm	52 to 350 gsm
	Bypass tray (Optional)	52 to 350 gsm ^{*2}	52 to 350 gsm ^{*2}	-
Paper capacity ^{*3}	High-capacity tray	2,100 sheets x 1-tray	2,100 sheets x 2-tray	2,100 sheets x 2-tray
	Bypass tray (Optional)	250 sheets	250 sheets	-
Power supply		Single-phase AC100-120 V +/- 10%, 2.5 A / AC220-240 V +/- 10%, 1.5 A, 50/60 Hz, ground connection	Single-phase AC100-120 V +/- 10%, 6 A / AC200-240 V +/- 10% 4 A, 50/60 Hz, ground connection	Single-phase AC100-120 V +/- 10%, 6 A / AC200-240 V +/- 10%, 4 A, 50/60 Hz, ground connection
Maximum power consumption		360 W (in case of 240 V)	880 W (in case of 240 V)	880 W (in case of 240 V)
Dimensions ^{*4}		W 988 x D 762 x H 992 mm	W 988 x D 762 x H 992 mm	W 988 x D 762 x H 992 mm
Weight		177 kg or less ^{*4}	232 kg or less ^{*4}	235 kg or less

Note: Optional bypass tray (Multi Sheet Inserter for Banner Print) is required for the High Capacity Feeder B1-S or High Capacity Feeder C3-DS.

Note: When connecting the High Capacity Feeder C3-DS and 2nd High Capacity Feeder C1-DS, the optional bypass tray (Multi Sheet Inserter for Banner Print) is attached to the left module.

*1: Post Card Kit is required to use paper with a width of less than 182 mm.

*2: Sheets longer than 488 mm can be used with weights from 52 to 220 gsm.

*3: 82 gsm paper.

*4: Including optional bypass tray (Multi Sheet Inserter for Banner Print).

Air Suction Feeder C1-DS / Chained Air Suction Feeder C1-DS (Optional)

Item		Description	
		Air Suction Feeder C1-DS	Chained Air Suction Feeder C1-DS-R + Chained Air Suction Feeder C1-DS-L
Paper size	High-capacity tray ^{*1}	Standard size: Max 13 x 19", SRA3, A3, Min 4 x 6", A5 Custom size: 98 x 148 mm to 330 x 488 mm	Standard size: Max 13 x 19", SRA3, A3, Min 4 x 6", A5 Custom size: 98 x 148 mm to 330 x 488 mm
	Bypass tray	Standard size: Max 13 x 19", SRA3, A3, Min A6, 5.5 x 8.5" Custom size: 90 x 146 mm to 330 x 660 mm	Standard size: Max 13 x 19", SRA3, A3, Min A6, 5.5 x 8.5" Custom size: 90 x 146 mm to 330 x 660 mm
Paper weight	High-capacity tray	52 to 400 gsm	52 to 400 gsm
	Bypass tray	52 to 350 gsm ^{*2}	52 to 350 gsm ^{*2}
Paper capacity ^{*3}	High-capacity tray	2,200 sheets x 2-tray	2,200 sheets x 2-tray x 2-connection
	Bypass tray	250 sheets	250 sheets
Power supply		Single-phase AC100-120 V +/- 10%, 6 A / AC200-240 V +/- 10%, 4 A, 50/60 Hz, ground connection	Single-phase AC100-120 V +/- 10 %, 6 A / AC200-240 V +/- 10 %, 4 A, 50/60 Hz, ground connection Single-phase AC100-120 V +/- 10 %, 6 A / AC200-240 V +/- 10 %, 4 A, 50/60 Hz, ground connection
Maximum power consumption		880 W (in case of 240 V)	880 W + 880 W (in case of 240 V)
Dimensions		W 988 x D 762 x H 992 mm	W 1,980 x D 762 x H 992 mm
Weight		194 kg or less	403 kg or less

Note: Bypass tray (Multi Sheet Inserter for Banner Print) is included.

*1: Post Card Kit for Air Suction Feeder is required to use paper with a width of less than 182 mm.

*2: Sheets longer than 488 mm can be used with weights from 52 to 220 gsm.

*3: 82 gsm paper.*3: 82 gsm paper.

Air Suction Feeder C1-DSXL / Chained Air Suction Feeder C1-DSXL (Optional)

Item		Description	
		Air Suction Feeder C1-DSXL + Banner Unit for Air Suction Feeder C1-DSXL	Chained Air Suction Feeder C1-DS-R + Chained Air Suction Feeder C1-DSXL-L + Banner Unit for Air Suction Feeder C1-DSXL
Paper size ^{*1}	High-capacity tray	[Upper tray] Standard size: Max 13 x 19", SRA3, A3, Min A4, Letter Custom size: 210 x 210 mm to 330 x 1,300 mm ^{*2} [Lower tray] Standard size: Max 13 x 19", SRA3, A3, Min 4 x 6", A5 Custom size: 98 x 148 mm to 330 x 488 mm	[Upper tray of the left module] Standard size: Max 13 x 19", SRA3, A3, Min A4, Letter Custom size: 210 x 210 mm to 330 x 1,300 mm ^{*2} [Lower tray of the left module, upper and lower tray of the right module] Standard size: Max 13 x 19", SRA3, A3, Min 4 x 6", A5 Custom size: 98 x 148 mm to 330 x 488 mm
	Bypass tray	Standard size: Max 13 x 19", SRA3, A3, Min A6, 5.5 x 8.5" Custom size: 90 x 146 mm to 330 x 660 mm	Standard size: Max 13 x 19", SRA3, A3, Min A6, 5.5 x 8.5" Custom size: 90 x 146 mm to 330 x 660 mm
Paper weight	High-capacity tray	52 to 400 gsm ^{*3}	52 to 400 gsm ^{*3}
	Bypass tray	52 to 350 gsm ^{*4}	52 to 350 gsm ^{*4}
Paper capacity ^{*5}	High-capacity tray	900 sheets ^{*6} + 2,200 sheets	2,200 sheets x 2-tray + 900 sheets ^{*6} + 2,200 sheets
	Bypass tray	250 sheets	250 sheets
Power supply		Single-phase AC100-120 V +/- 10%, 6 A / AC200-240 V +/- 10%, 4 A, 50/60 Hz, ground connection	Single-phase AC100-120 V +/- 10 %, 6 A / AC200-240 V +/- 10 %, 4 A, 50/60 Hz, ground connection Single-phase AC100-120 V +/- 10 %, 6 A / AC200-240 V +/- 10 %, 4 A, 50/60 Hz, ground connection
Maximum power consumption		880 W (in case of 240 V)	880 W + 880 W (in case of 240 V)
Dimensions		W 1,580 x D 762 x H 992 mm	W 2,572 x D 762 x H 992 mm
Weight		213 kg or less	420 kg or less

Note: Bypass tray (Multi Sheet Inserter for Banner Print) is included.

Note: Air Suction Feeder C1-DSXL can feed long sheet only from the Upper tray.

Note: Chained Air Suction Feeder C1-DSXL-L can feed long sheet only from the Upper tray.

*1: Post Card Kit for Air Suction Feeder is required to use paper with a width of less than 182 mm.

*2: Up to 330 x 864 mm paper is supported in duplex automatic printing.

*3: Paper length 488+ to 660 mm: 52 to 350 gsm, 660+ to 864 mm: 52 to 300 gsm, 864+ to 1,200 mm: 52 to 256 gsm. 1,200+ to 1,300 mm can only be used for certain brands of 104 gsm. Duplex automatic printing supports paper weight up to 300 gsm.

*4: Sheets longer than 488 mm can be used with weights from 52 to 220 gsm.

*5: 82 gsm paper.

*6: Up to 100 sheets (82 gsm) of paper longer than 864 mm can be used.

Offset Catch Tray / Long Catch Tray (Optional)

Item	Description	
	Offset Catch Tray	Long Catch Tray
Paper size	90 x 146 mm to 330 x 660 mm ^{*1}	90 x 146 mm to 330 x 1,300 mm ^{*2}
Paper weight	52 to 400 gsm	52 to 400 gsm
Tray capacity ^{*3}	500 sheets	300 sheets (Paper length up to 488 mm) 100 sheets (Paper length above 488 to 864 mm) 10 sheets (Paper length above 864 to 1,300 mm)
Dimensions	W 406 x D 393 x H 184 mm	W 512 x D 396 x H 308 mm ^{*4}
Weight	6 kg or less	4 kg or less ^{*5}

Note: Catch Tray Fan Kit (optional) are required.

*1: Tray capacity is not guaranteed larger than 330 x 488 mm sheet.

*2: Up to 330 x 660 mm sheet can be accommodated when Long Paper Extension Kit is not installed.

*3: 82 gsm paper.

*4: When Long Paper Extension Kit is installed, W 941 x D 396 x H 495 mm.

*5: When Long Paper Extension Kit is installed, 5 kg or less.

Folder Unit CD3 (Optional)

Item		Description
Z fold half sheet	Paper size	A3, 11 x 17", JIS B4
	Paper weight	60 to 90 gsm
Trifold	Paper size	A4, Letter
	Paper weight	60 to 90 gsm
	Tray capacity [*]	30 sheets
Power supply		Single-phase AC100-240 V +/- 10 %, 1 A (100 V) / 0.5 A (240 V), 50/60 Hz, ground connection
Maximum power consumption		120 W (in case of 240 V)
Dimensions		W 232 x D 588 x H 992 mm
Weight		52 kg or less

Note: Folder Unit CD3 is an option for Finisher-C5 and Finisher-C5 with Booklet Maker.

*1: 82 gsm paper.

Finisher-C5 / Finisher-C5 with Booklet Maker (Optional)

Item		Description	
		Finisher-C5 + Transport Unit v2	Finisher-C5 with Booklet Maker + Transport Unit v2
Type	Output tray	Sort (Offset available) / Stack (Offset available)	
	Finishing tray	Sort (Offset available) / Stack (Offset available)	
	Booklet tray	-	Sort / Stack
Paper size ^{*1}	Output tray	90 x 146 mm ^{*2} to 330 x 1,300 mm ^{*3}	
	Finishing tray	203 x 148 mm to 330 x 488 mm	
Paper weight ^{*1}	Output tray	52 to 350 gsm ^{*4,5}	
	Finishing tray	52 to 350 gsm ^{*5}	
Tray capacity ^{*6}	Output tray	500 sheets (A4) ^{*3}	
	Finishing tray	[Without stapling] A4: 3,000 sheets JIS B4 or larger: 1,500 sheets A5: 1,000 sheets Mixed size stacking ^{*7} : 300 sheets [With stapling] A4: 200 sets (Single stapling), 100 sets (Dual stapling) or 3,000 sheets JIS B4 or larger: 100 sets or 1,500 sheets A5: 100 sets or 1,000 sheets (Single stapling), 75 sets or 750 sheets (Dual stapling) Mixed size stacking ^{*7} : 70 sets or 200 sheets	[Without stapling] A4: 1,500 sheets JIS B4 or larger: 1,500 sheets A5: 1,000 sheets Mixed size stacking ^{*7} : 300 sheets [With stapling] A4: 200 sets (Single stapling), 100 sets (Dual stapling) or 1,500 sheets JIS B4 or larger: 100 sets or 1,500 sheets A5: 100 sets or 1,000 sheets (Single stapling), 75 sets or 750 sheets (Dual stapling) Mixed size stacking ^{*7} : 70 sets or 200 sheets
	Booklet tray	-	20 sets ^{*8}
Staple	Staple capacity	Staple: Max 50 sheets (90 gsm or less) ^{*9} Staple-free staple ^{*10} : Max 10 sheets (80 gsm or less)	
	Paper size ^{*11}	[Single stapling, Dual stapling / Staple-free stapling ^{*10}] Standard size: Max A3, 11 x 17", Min A5, 6 x 9" Custom size: 203 x 148 mm to 297 x 432 mm [4 stapling] Standard size: A4, Letter	
	Paper weight	Staple: 52 to 350 gsm Staple-free staple ^{*10} : 60 to 105 gsm	
	Staple position	Single stapling, Dual stapling, 4 stapling	
Punch ^{*12}	Number of holes	2-hole / 4-hole punch or 2-hole / 3-hole punch (US specifications)	
	Paper size ^{*13}	Standard size: 2-hole punch Max A3, 11 x 17", Min A5, 7.25 x 10.5" 3-hole punch Max A3, 11 x 17", Min JIS B5, 7.25 x 10.5" 4-hole punch Max A3, 11 x 17", Min A4, 7.25 x 10.5" Custom size: 2-hole punch 203 x 148 mm to 297 x 432 mm 3-hole punch 254 x 148 mm to 297 x 432 mm 4-hole punch 267 x 148 mm to 297 x 432 mm	
	Paper weight	52 to 220 gsm	
Booklet finishing	Booklet finishing capacity ^{*14}	-	Saddle staple: 20 sheets (90 gsm or less) Single fold: 5 sheets (90 gsm or less)
	Paper size	-	Standard size: Max 13 x 18", SRA3, A3, Min JIS B5, 7.25 x 10.5" Custom size: 182 x 257 mm to 330 x 457 mm
	Paper weight	-	Saddle staple: 60 to 300 gsm Single fold: 60 to 300 gsm
Dimensions ^{*15}	W 771 x D 692 x H 1,054 mm		W 776 x D 692 x H 1,054 mm
Weight	53 kg or less		65 kg or less

*1: Without stapling, punching or booklet finishing.

*2: When using 90x146mm, please check the print run in advance.

*3: Tray capacity is not guaranteed larger than 330 x 488 mm sheet.

*4: Sheets longer than 488 mm can be used with weights from 52 to 220 gsm.

*5: 52 to 220 gsm paper may not be aligned properly depending on the paper type.

*6: 82 gsm paper.

*7: When larger size sheets are stacked on top of smaller size sheets.

*8: When printing on the same size of paper.

*9: Up to 65 sheets can be stapled when the optional Finisher-C Staple Unit 65 Sheets is installed. However incorrect stapling such as uneven edge alignment may occur depending on the paper type.

*10: Staple-free stapling does not have binding force equal to stapled stapling. Bound part may be easily separated depending on the paper type, temperature, humidity, and how the page is turned over.

*11: Staple positions available depends on the paper size.

*12: Punching function is provided as standard.

*13: The number of punch holes available depends on the paper size.

*14: The number of sheets that can be booklet finished varies depending on the paper weight. Booklet may not be tightly closed depending on the size or type of the paper.

*15: When the extension tray is pulled out.

Interface Decurler Module D1 (Optional)

Item	Description
Power supply	Single-phase AC100-240 V +/- 10 %, 2.5 A (100 V) / 1 A (240 V), 50/60 Hz, ground connection
Maximum power consumption	250 W (in case of 240 V)
Dimensions	W 340 x D 725 x H 992 mm
Weight	40 kg or less

Note: Interface Decurler Module D1 is necessary for connecting High Capacity Stacker A2, High Capacity Stacker A2 with Transport Module, Finisher D6, or Finisher D6 with Booklet Maker to the printer.

Insertor D1 (Optional)

Item	Description
Paper size	Standard size: Max 12.6 x 19.2", SRA3, A3, Min A5, 6 x 9" Custom size: 182 x 148 mm to 330 x 488 mm
Paper weight	52 to 350 gsm
Paper capacity *1	250 sheets
Power supply	Supplied from Interface Decurler Module D1
Dimensions	W 700*2 x D 725 x H 1,235 mm
Weight	45 kg or less

Note: High Capacity Stacker A2, High Capacity Stacker A2 with Transport Module, Finisher D6, or Finisher D6 with Booklet Maker is required.

*1: 82 gsm paper.

*2: The width of only the paper transfer part is 165 mm.

Static Eliminator D1 (Optional)

Item	Description
Power supply	Single-phase AC100-240 V +/- 10 %, 0.6 A (100 V) / 0.3 A (240 V), 50/60 Hz, ground connection
Maximum power consumption	72 W (in case of 240 V)
Dimensions	W 232 x D 725 x H 992 mm
Weight	40 kg or less

Note: High Capacity Stacker A2, High Capacity Stacker A2 with Transport Module, Finisher D6 or Finisher D6 with Booklet Maker is required.

Smart Monitoring Gate D1 (Optional)

Item	Description
Power supply	Single-phase AC100-240 V +/- 10 %, 2.4 A (100 V) / 1.2 A (240 V), 50/60 Hz, ground connection
Maximum power consumption	240 W (in case of 240 V)
Dimensions	W 605 x D 725 x H 992 mm
Weight	92 kg or less

Note: High Capacity Stacker A2, High Capacity Stacker A2 with Transport Module, Finisher D6 or Finisher D6 with Booklet Maker is required.

High Capacity Stacker A2 / High Capacity Stacker A2 with Transport Module (Optional)

Item		Description	
		High Capacity Stacker A2	High Capacity Stacker A2 with Transport Module
Tray capacity* ¹	Output tray	500 sheets* ²	
	Stacker cart	5,000 sheets or stacking height is less than 570 mm.	
Paper size	Output tray	90 x 146 mm* ³ to 330 x 1,300 mm* ²	
	Stacker cart	203 x 182 mm to 330 x 488 mm	
Paper weight	Output tray	52 to 400 gsm* ⁴	
	Stacker cart	52 to 300 gsm	
Power supply		Single-phase AC100-240 V +/- 10 %, 1.5 A (100 V) / 0.8 A (240 V), 50/60 Hz, ground connection	
Maximum power consumption		192 W (in case of 240 V)	
Dimensions		W 800 x D 725 x H 1,042 mm	W 848 x D 725 x H 1,042 mm
Weight* ⁵		155 kg or less	159 kg or less

Note: Interface Decurler Module D1 is required.

Note: High Capacity Stacker A2 with Transport Module is an option for connecting a third party vendor finisher. For a third party vendor finisher, please contact your local FUJIFILM representative.

*1: 82 gsm paper.

*2: Tray capacity is not guaranteed larger than 330 x 488 mm sheet. When the optional Banner Print Extension Kit is installed, 250 sheets of up to 330 x 488 mm, 100 sheets of up to 330 x 864 mm, 10 sheets of up to 330 x 1,300 mm paper can be accommodated.

*3: When using 90x146mm, please check the print run in advance.

*4: Sheets longer than 488 mm can be used with weights from 52 to 220 gsm.

*5: Including a Stacker Cart.

Crease/Two-sided Trimmer D2 (Optional)

Item		Description
Two-sided trim	Paper size	194 x 210 mm to 330 x 488 mm
	Paper weight	52 to 350 gsm
	Trim dimensions	One side: 6 to 25 mm
Crease	Paper size	182 x 210 mm to 330 x 488 mm
	Paper weight* ¹	60 to 350 gsm
	Number of crease lines* ²	1 to 5
Power supply		Single-phase AC100-240 V +/- 10 %, 4.0 A (100 V) / 2.0 A (240 V), 50/60 Hz, ground connection
Maximum power consumption		480 W (in case of 240 V)
Dimensions		W 605 x D 725 x H 992 mm
Weight		128 kg or less

Note: Finisher D6 or Finisher D6 with Booklet Maker is required.

*1: When creasing with booklet finishing. In case of creasing a single sheet without folding, 157 gsm or more paper can be used.

*2: The continuous print speed will decrease significantly as the number of creasing lines increases.

Folder Unit CD2 (Optional)

Item		Description
Z Fold half sheet	Paper size	A3, 11 x 17", JIS B4
	Paper weight	60 to 90 gsm
Trifold	Paper size	A4, Letter
	Paper weight	60 to 90 gsm
	Tray capacity ^{*1}	30 sheets
Power supply	Single-phase AC100-240 V +/- 10 %, 1 A (100 V) / 0.5 A (240 V), 50/60 Hz, ground connection	
Maximum power consumption	120 W (in case of 240 V)	
Dimensions	W 232 x D 725 x H 992 mm	
Weight	55 kg or less	

Note: Folder Unit CD2 is an option for Finisher D6 and Finisher D6 with Booklet Maker.

*1: 82 gsm paper.

Finisher D6 / Finisher D6 with Booklet Maker (Optional)

Item		Description	
		Finisher D6	Finisher D6 with Booklet Maker
Type	Output tray	Sort / Stack	
	Finishing tray	Sort (Offset available) / Stack (Offset available)	
	Booklet tray	-	Sort / Stack
Paper size* ¹	Output tray	90 x 146 mm ² to 330 x 1,300 mm ³	
	Finishing tray	148 x 146 mm to 330 x 488 mm	
Paper weight* ¹	Output tray	52 to 400 gsm ⁴	
	Finishing tray	52 to 350 gsm	
Tray capacity* ⁵	Output tray	500 sheets (A4)	
	Finishing tray	[Without stapling] A4: 3,000 sheets JIS B4 or larger: 1,500 sheets Mixed size stacking* ⁶ : 350 sheets [With stapling] A4: 200 sets or 3,000 sheets JIS B4 or larger: 100 sets or 1,500 sheets	[Without stapling] A4: 2,000 sheets JIS B4 or larger: 1,500 sheets Mixed size stacking* ⁶ : 350 sheets [With stapling] A4: 200 sets or 2,000 sheets JIS B4 or larger: 100 sets or 1,500 sheets
	Booklet tray	-	20 sets (16 sheets/set or less) ⁷
Staple	Staple capacity	Max 100 sheets (90 gsm or less) ⁸	
	Paper size* ⁹	Standard size: Max A3, 11 x 17", Min A5, 8 x 10" Custom size: 182 x 146 mm to 297 x 432 mm	
	Paper weight	52 to 350 gsm	
	Staple position	Single stapling, Dual stapling, 4 stapling	
Punch* ¹⁰	Number of holes	2-hole / 4-hole punch or 2-hole / 3-hole punch (US Specifications)	
	Paper size* ¹¹	Standard size: 2-hole punch Max A3, 11 x 17", Min JIS B5, 8 x 10" 3-hole punch Max A3, 11 x 17", Min JIS B5, 8 x 10" 4-hole punch Max A3, 11 x 17", Min A4, Letter Custom size: 2-hole punch 203 x 182 mm to 297 x 432 mm 3-hole punch 254 x 182 mm to 297 x 432 mm 4-hole punch 267 x 182 mm to 297 x 432 mm	
	Paper weight	52 to 220 gsm	
Booklet finishing	Booklet finishing capacity* ¹²	-	Saddle staple: Max 30 sheets (90 gsm or less) Single fold: Max 5 sheets (220 gsm or less)
	Paper size	-	Standard size: Max 13 x 19", SRA3, A3, Min JIS B5, 7.25 x 10.5" Custom size: 182 x 257 mm to 330 x 488 mm
	Paper weight	-	60 to 350 gsm
Power supply	Single-phase AC100-240 V +/- 10 %, 3.0 A (100 V) / 1.5 A (240 V), 50/60 Hz, ground connection		
Maximum power consumption	360 W (in case of 240 V)		
Dimensions	W 855 x D 725 x H 1,204 mm	W 892 x D 725 x H 1,204 mm	
Weight	87 kg or less	107 kg or less	

Note: Interface Decurler Module D1 is required.

*1: Without stapling, punching or booklet finishing.

*2: When using 90x146mm, please check the print run in advance.

*3: Tray capacity is not guaranteed larger than 330 x 488 mm sheet. When the optional Banner Print Extension Kit is installed, 150 sheets of up to 330 x 660 mm, 100 sheets of up to 330 x 864 mm, 10 sheets of up to 330 x 1,300 mm paper can be accommodated.

*4: Sheets longer than 488 mm can be used with weights from 52 to 220 gsm.

*5: 82 gsm paper.

*6: When larger size sheets are stacked on top of smaller size sheets.

*7: Booklet tray capacity is 16 sets (17-20 sheets/set), 12 sets (21-25 sheets/set) and 10 sets (26-30 sheets/set).

*8: Up to 65 sheets can be stapled for paper sizes exceeding A4 or letter.

*9: Staple positions available depends on the paper size.

*10: Optional.

*11: The number of punch holes available depends on the paper size.

*12: The number of sheets that can be booklet finished varies depending on the paper weight. Booklet may not be tightly closed depending on the size or type of the paper.

Square Back Fold Trimmer D1 (Optional)

Item		Description
Paper size		Same as the “paper size” of the Finisher D6 Booklet Finishing.
Paper weight		Same as the “paper weight” of the Finisher D6 Booklet Finishing.
Booklet tray capacity*1		Max 20 sets (16 sheets/set or less)*2
Face trim	Face trim capacity*3	Saddle staple: Max 30 sheets, Single fold: Max 5 sheets
	Face trim dimensions	2 to 20 mm
Square back fold capacity*3 *4		Max 30 sheets
Power supply		Single-phase AC100-240 V +/- 10 %, 1.0 A (100 V) / 0.6 A (240 V), 50/60 Hz, ground connection
Maximum power consumption		144 W (in case of 240 V)
Dimensions		W 1,066 x D 725 x H 552 mm
Weight		100 kg or less

Note: Finisher D6 with Booklet Maker is required.

*1: Paper may not be accepted depending on paper type and other usage conditions.

*2: Booklet tray capacity is 16 sets (17-20 sheets/set), 12 sets (21-25 sheets/set) and 10 sets (26-30 sheets/set).

*3: The capacity can decrease depending on type and weight of paper being used and other conditions.

*4: Square back folding does not support single-folded sheets and less than 5 sheets of saddle-stapled paper.

Notes

- Performance is not guaranteed for all paper types. Please contact your local FUJIFILM representative for recommended paper.
- Functional spare parts will be available for at least 7 years after the product is no longer manufactured.

fujifilm.com/fb

FUJIFILM

FUJIFILM Business Innovation Corp.

7-3, Akasaka 9-Chome, Minato-ku Tokyo 107-0052, Japan

Trademarks •FUJIFILM and FUJIFILM logo are registered trademarks or trademarks of FUJIFILM Corporation. •Revorvia, Revorvia logo, Revorvia Press and Revorvia Flow are registered trademark or trademark of FUJIFILM Business Innovation Corp. •Adobe, Adobe logo, PostScript and PostScript logo, Adobe PDF, Adobe PDF Print Engine are either registered trademarks or trademarks of Adobe in the United States and/or other countries. •All product names and company names mentioned in this brochure are trademarks or registered

The information is as of April 2026