

## **FUJINON**

Ver 2.3

|                          | Ver.2.                                     |                      |
|--------------------------|--|----------------------|
| 型番                       | <b>Product Name</b>                        | <b>CF16ZA-1S</b>     |
| 作。占见Fght [*****]         | Focal length [mm]                          | 16                   |
| 焦点距離 [mm]                | (design value)                             | (16.42)              |
| 絞り範囲 (F値)                | Iris range (Fnumber)                       | F1.8-F16             |
| 画角 (H×V)                 | Angle of view                              | 47.3° × 36.1° (1.1") |
| フォーカス範囲 (レンズメカ先端より) [mm] | Working distance                           | ∞ - 100              |
|                          | (from front of lens barrel) [mm]           |                      |
| 操作方法:フォーカス               | Operation of focus                         | Manual               |
| 操作方法:アイリス                | Operation of iris                          | Manual               |
| フィルタ径 [mm]               | Filter thread [mm]                         | M37.5 × 0.5          |
| マウント                     | Mount                                      | C-mount              |
| 質量 (約) [g]               | Weight (approx.) [g]                       | 180                  |
| 適合センサーサイズ (標準)           | Sensor size (std.)                         | 1.1" (2.5μm)         |
| 適合センサーサイズ(最大)            | Sensor size (max.)                         | 1.2" (2.74µm)        |
| バックフォーカス(空気換算長)[mm]      | Back focal length (in air) [mm]            | 21.85                |
| フランジバック [mm]             | Flange back [mm]                           | 17.53                |
| 入射瞳位置(マウント面から)[mm]       | Entrance pupil position                    | -48.25               |
|                          | (from Mount) [mm]                          |                      |
| 射出瞳位置 (結像面より) [mm]       | Exit pupil position                        | -88.43               |
|                          | (from image plane) [mm]                    |                      |
| 前側主点 (マウント面から) [mm]      | Front principal point (from Mount) [mm]    | -35.21               |
| 後側主点 (マウント面から) [mm]      | Rear principal point (from Mount) [mm]     | 1.10                 |
| 主点間隔 [mm]                | Distance between the principal points [mm] | 36.31                |
| TVディストーション [%]           | TV distortion [%]                          | -0.8                 |
| 外形寸法 [mm]                | Dimension [mm]                             | φ39 × 67.6           |
| 主光線入射角度[°]               | Chief Ray Angle [°]                        | 4.93                 |
| 周辺光量比 (F4.0·対角端) [%]     | Relative illumination [%]                  |                      |
|                          | (Aperture: F4.0,                           | 92                   |
|                          | Image height: at diagonal)                 |                      |
| 周辺光量比(開放•対角端)[%]         | Relative illumination [%]                  |                      |
|                          | (Aperture: at full open,                   | 36                   |
|                          | Image height : at diagonal)                |                      |
| 使用温度範囲                   | Operation Temperature Range                | -10°C ∼ +50°C        |
| 保存温度範囲                   | Storage Temperature Range                  | -30°C ∼ +60°C        |

These specifications are subject to change without notice.

Entrance pupil position and Exit pupil position are calculated by "chief ray of 60% image height".